

The electronic anti-scale system

Your green alternative to water softeners



German Technology Absolutely Magnetism-Free



Quality - Made in Germany

Physical water treatment with Christiani Wassertechnik GmbH

Christiani Wassertechnik GmbH - CWT - was established in 1948. Today, it is one of the oldest manufacturers of physical water treatment in the world. The family-run business is headquartered in Berlin, Germany. CWT has more than 30 years of experience in the development and production of anti-scale systems and its products are available in over 50 countries world-wide.

Vulcan offers an eco-friendly technology that comes with an outstanding quality commitment and a ten-year warranty. It solves problems with hard water in residential, commercial and industrial applications.

Quality - Made in Germany







Over 30 years of experience in physical water treatment

Christiani Wassertechnik GmbH The managing directors







Rolf Christiani

Jessica Christiani

Cedric Christiani

Table of contents

Vulcan - Against scale and rust

Vulcan - against scale and rust2	Installation Instructions			
The scale and rust problem4	FAQs - Frequently asked questions 14			
The 3 Vulcan effects5	Installation notes and examples15			
	Installation instructions - Residential Line 16			
Residential Line	Installation instructions			
Vulcan 3000 / Vulcan 5000	Commercial and Industrial Line			
Application areas and technical data8				
Benefits9	References			
	Client list			
Commercial Line	Models and sizes21			
Vulcan S10 / S25 / S100				
Application areas and technical data10				
Benefits11				
Industrial Line				
Vulcan S250 / S500				
Application areas and technical data				
Benefits				


Vulcan – Against scale and rust

The eco-friendly alternative to water softeners

Vulcan provides you with an eco-friendly water treatment system which protects your water pipes and equipment against scale and rust. The method is based on the patented Vulcan-Impulse-Technology and treats your water without applying any chemicals or salt.

Special electronic impulses change the crystallization process of the calcium in hard water, causing the particles to lose their ability to stick to surfaces.

- ✓ Important minerals remain in the water
- Maximum working life of machinery and equipment
- Reduction of scale deposits in the whole piping system
- ✓ 10-year warranty
- √ Made in Germany



Model sizes from 1/2" up to 20" pipe diameter

Vulcan is a customized solution for your individual needs. The various product lines of Vulcan solve problems in residential use, commercial applications and in industrial settings.



Benefits

Vulcan solves scale and rust problems

- Eco-friendly solution against scale problems
- No use of salt or chemicals
- Suitable for pipe diameters from 1/2" up to 20"

CWT Quality - Made in Germany

- Fully cast in acrylic for optimal quality endurance
- Maintenance-free

- Do-it-Yourself installation no need to cut the pipes
- Works on every pipe material iron, copper, stainless steel, galvanized iron, plastic, PVC, PE-x, compound pipes in any material mixture, etc.

Industrial Line

Vulcan S250

Manufactured by a 3rd generation family business Over 30 years of experience in physical water treatment International 10-year product warranty Available in over 50 countries Tested by independent institutes cULus, TÜV Nord and CE certified

The scale and rust problem

The water we use in our private houses as well as in commercial and industrial facilities contains dissolved scale consisting of calcium and magnesium.

When exposed to a temperature increase or change of pressure, the calcium crystallizes and builds incrustations. These hard scale deposits appear often in places where water is heated, swirls around or leaves the pipes.



Pipe with scale deposits

The longer you wait to take action against these problems, the more damages and costly repairs will arise. Soon you will have to replace the whole piping system and buy new equipment.



Tube heat exchanger



Washing machine heating element

Scale deposits on the inside of pipes, on heating elements or on expensive machinery create many problems.



Water feeder with biofilm

Scale-related problems

- Loss of energy due to a longer heating process
- High costs of repairs and maintenance on machines and equipment
- Loss of water pressure due to decreased pipe diameters
- High cleaning costs and need for aggressive cleaning agents
- Decrease in overall industrial productivity



Heating element

The Vulcan treatment effects – before and after



Grill plate in a professional kitchen



Swimming pool water line



Cooling tower grid



Pool chlorinator



Toilet bowl



Grease trap



Greenhouse plants





The 3 Vulcan effects

1. Vulcan stops scaling in pipes and appliances

Without the Vulcan water treatment, scale particles in the water form sticky crystals that then build solid deposits. The Vulcan-Impulse-Technology modifies the crystallization of calcium and magnesium using the natural process of electrophoresis. The crystals become smoother and rod-shaped and can no longer attach to each other. The more rod-shaped crystals that are created, the stronger the positive effect of scale-prevention. Scale is now washed away in the water as a fine powder.

1st Vulcan effect

Vulcan modifies the structure of the calcium crystals



2. Vulcan gently sanitizes the piping system

The Vulcan water treatment changes the balance between the scaling process and natural resolving process. Mono-crystals can no longer form deposits, therefore the scale build-up process is reduced. The natural scale resolving process now needs only to deal with existing deposits and can effectively combat them. Thus scale is removed faster than it forms. The natural surplus of carbonic acid dissolves the scale from the scale. Gradually and carefully, the deposits in the pipes are cleaned out.



2nd Vulcan effect

Vulcan removes scale deposits in the piping system



3. Vulcan protects against rust damage and perforation

Copper and/or iron oxidation occurs in all metal pipes through contact with hard water. These oxides seriously affect the pipe surfaces and often lead to corrosion.

The Vulcan-Impulse-Technology generates an electrophoresis-effect which produces a protective metal-carbonate layer. According to the material of the pipe, this layer consists of copper carbonate, iron carbonate or zinc carbonate and settles on all shiny metal surfaces. It protects the pipe from harmful substances which could lead to corrosion.

3rd Vulcan effect

Vulcan produces a protective metalcarbonate layer





Residential Line

The Vulcan Residential Line units have been designed to protect the piping system in private houses and small commercial equipment, such as coffee machines and dishwashers. These units can easily be installed within a few minutes.

Houses and buildings

The piping system, water heaters, washing machines and other appliances are protected.

Pools & Jacuzzis

Vulcan protects the equipment and pipes against harmful deposits. You can cut down on chlorine use and many other additives.



Water heaters and heat exchangers

Vulcan controls scale build-up in tankless water heaters and reduces their maintenance.

Solar water heater

Vulcan reduces scale build-up in collectors, it protects hot water tanks and vacuum tubes, and keeps the system from over-heating.



Vulcan 3000



 $\begin{array}{ll} \text{Max. pipe diameter} & 11_2'' \\ \text{Max. capacity} & 800 \text{ gph (3000 l/h)} \\ \text{Wattage} & 2.0 \text{ Watt} \\ \text{Impulse bands} & 2 \times 3' 3'' (2 \times 1 \text{ m}) \end{array}$

Vulcan 5000



 Max. pipe diameter
 2"

 Max. capacity
 1350 gph (5000 l/h)

 Wattage
 2.0 Watt

 Impulse bands
 2 x 3" 3" (2 x 1 m)

Application areas

- Houses and apartments
- Drinking water
- Bungalows and resorts
- Swimming pools & jacuzzis
- Small machinery
- Irrigation systems
- Sprinklers
- And many more

SALT OR CHEMICAL

Benefits







- Reduction of scale deposits throughout the whole piping system
- ✓ Eco-friendly system without chemicals or salt
- √ Faster cleaning of kitchen and bathroom

- ✓ Important minerals remain in the water
- ✓ Gardening systems and sprinklers stay clean and last longer
- Considerable savings on washing and cleaning agents
- ✓ Less time and effort spent on repairs and maintenance at your home, e.g. water heaters, washing machines, etc.
- Reduction of harmful bacteria and biofilm



Commercial Line

The Commercial Line units treat pipe diameters up to 6" and have been designed to perfectly meet the requirements of small and large commercial facilities. These programmable units allow for individual adjustment according to the materials and diameters of the pipes.

Application areas

Buildings and housing

Condominiums & large buildings Educational institutions Public swimming pools Golf courses Fitness clubs

Medical

Hospitals Nursing homes Residences



Agriculture

Plants Livestock Irrigation systems Machinery And many more

Hospitality

Hotels and resorts Restaurants and cafés Passenger ships, maritime And many more



Vulcan S10



 Max. pipe diameter
 3"

 Max. capacity
 45 gpm (10 m³/h)

 Wattage
 2.25 Watt

 Impulse bands
 2 x 3' 3" (2 x 1 m)

 Programs
 3

Vulcan S25



 Max. pipe diameter
 4"

 Max. capacity
 110 gpm (25 m³/h)

 Wattage
 2.25 Watt

 Impulse bands
 4 x 6' 7" (4 x 2 m)

 Programs
 5

Vulcan S100



Max. pipe diameter Max. capacity Wattage Impulse bands Programs 6" 450 gpm (100 m³/h) 2.5 Watt 6 x 13' 2" (6 x 4 m) 10

Benefits







- Maximum working life of commercial machinery and equipment
- √ Reduction of harmful bacteria and biofilm
- ✓ Less time and effort spent on cleaning

- Reduction of maintenance on irrigation systems and water tapping
- Food and beverages keep their natural taste
- More reliable water supply within sanitary facilities
- ✓ Savings due to more efficient use of energy for heating water



Industrial Line

The Industrial Vulcan units treat pipe diameters up to 20" and have been designed to provide solutions for all kinds of applications in light and heavy industries. The customized adjustment to pipe diameters and pipe materials is based on 10 different system-integrated programs.

Application areas

Printing industry

Hospitals Cooling towers

Aluminium industry Heat exchangers

Chemical manufacturing Food production

Lumber industry Maritime and cargo industry

Car industry Textile industry

Rubber production Refineries

Injection molding Waste water treatment





And many more

Vulcan S250



Max. pipe diameter 10'

Max. capacity 1100 gpm (250 m³/h) Wattage 2.75 Watt

Impulse bands 8 x 32′ 9″ (8 x 10 m)
Programs 10

Vulcan S500



Max. pipe diameter 2

Max. capacity 2200 gpm (500 m³/h) Wattage 3.25 Watt

Impulse bands 10 x 98′ 5″ (10 x 30 m)

Programs 10



Benefits







- ✓ Productivity increase due to the reduction of lime incrustations
- √ Inexpensive installation without interruption of the production process
- √ Spend less on machinery maintenance

- √ Fast amortization of acquisition costs
- √ Easy cleaning and no need to apply acids in cooling towers
- √ Reduces chemical use in many areas

- √ Maximum working life of expensive production equipment
- √ More reliable water supply



FAQs - Frequently asked questions

How do I choose the right model size? Please check the pipe diameter in the area where you want to install Vulcan. Then choose the unit that is designed for this size.

Do copper or synthetic pipes need a scale protection device at all? Yes. Copper and plastic pipes are prone to calcifications, too. The smoother a surface is the longer it can resist the process of calcification, but once a first layer of scale has built up, the incrustation process proceeds just as fast as on any other surface.

Up to which degree of water hardness can Vulcan be applied? Vulcan operates within a high performance frequency range. It can thus be successfully applied even on water with a particularly high degree of hardness.

Does the Vulcan treatment have a softening effect on the water? As the water treated by Vulcan does not lose any minerals, such as calcium and magnesium, the composition of the water remains unaltered. It feels noticeably softer, though. You are sure to feel this effect when showering or washing your hair. The treatment does not change the measured water hardness, but modifies the shape of its components.

How long does it take Vulcan to sanitize the pipes? Vulcan removes scale and rust slowly without negatively affecting the pipes. The cleaning process takes about as long as it took the incrustations to develop.



Which pipe materials are the devices suitable for? Vulcan is suitable for all pipe materials: iron, copper, plastic, stainless steel, PVC, compound pipes, PE-X, etc.

Which voltage range is the electronic plug-in power supply unit suitable for? All Vulcan power supply units are suitable for voltage ranges between 87 Volt – 260 Volt and 50 Hz – 60 Hz. They operate on 24 VDC.

What are the power costs of Vulcan per year? Vulcan is completely maintenance-free. The cost of electric energy per year amounts to approx. US $\$ 3 - 7 (2-6 \ \ \)$.

Installation Examples

- 1. For optimal water treatment Vulcan is best installed near the water meter or at the main water supply.
- The impulse band windings can be placed on the left side, on the right side or underneath the electronic device. Leave a safe distance of at least 1/2" (1 cm) between the bands.
- Vulcan can be installed vertically, horizontally or at any other angle. If there is no space available on the pipe the electronic block can also be wall-mounted.
- 4. In case of limited space the windings can be placed partly on the main pipe and partly on the distributor pipe.

All these different installations are possible because the treatment impulses extend over several meters to either side of the pipes.

Vulcan Vulcan Vulcan

Installation Notes


- 1. Protect the power supply unit against exposure to direct water.
- 2. Use the included switching power supply unit only.
- 3. Do not cut the impulse bands nor the 24 V power cord of the power supply unit.
- 4. Do not remove the end caps or the impulse band insulation.
- 5. The operating temperature of Vulcan ranges from -13°F to 122°F (-25°C to +50°C).
- 6. Clean the device with water only.
- Temperature peaks on heating element surfaces should not exceed 203°F (95°C).




Installation Instructions - Residential Line

- 1. Put the two cable clips through the fixing holes at the bottom of the electronic device. Now place the device onto the pipe. Use the cable clips to latch the device to the pipe.
- Connect one of the impulse bands to the device and use another cable clip to latch it to the pipe.
- Wind the impulse bands around the pipe producing a coil. Make sure you wind the band tightly to the pipe and place the windings close to each other.

- Latch the end of the impulse band to the pipe using another cable clip.
 Now repeat the procedure with the second impulse band.
- 5. First plug the connector into the upper right in-jack of the device and then connect the power supply unit with an electrical outlet.
- The red pilot lights will illuminate as soon as the device starts to operate.
 Vulcan works from now on maintenance-free.







Installation Instructions - Commercial Line and Industrial Line

- Put the two cable clips through the fixing holes at the bottom of the electronic device. Now place the device onto the pipe. Use the cable clips to latch the device to the pipe.
- 2. Plug one of the impulse bands into the bottom impulse band in-jack and latch it to the pipe using another cable clip.
- Wind the impulse band around the pipe producing a coil. Make sure you wind the band tightly to the pipe and place the windings close to each other.
- Latch the end of the band to the pipe using another cable clip. Now plug another impulse band into the in-jack on the opposite side and repeat the procedure.

- Plug another impulse band into the next impulse band in-jack and, according to the device type, repeat steps
 4 until all impulse bands are in use. All impulse bands must be wound tightly around the pipe and fastened with cable clips.
- First plug the connector into the upper right in-jack of the device and then connect the power supply unit with an electrical outlet.
- 7. Programming: Set the programm by touching the twin metal sensors on the left side simultaneously.







CWT - Christiani Wassertechnik GmbH Herr Rolf Christiani Köpenicker Str. 154 10997 Berlin Germany



We have been using Vulcan water treatment equipment in our ice hockey hall Hartwall Arena since 2003.

We are using many sizes of several heating/cooling equipment in our water system:

- Vulcan 5000
- Vulcan S25
- Vulcan S100

We have realibility with these systems and have been most satisfied in using them.

Vulcan is a high-quality and great solution to different kind of premise.

Sincerly,

Hartwall Arena







References

Philipp Best Plumbing

All your Commercial & Industrial Plumbing Needs

CWT - Physical water treatment system

I've been in the plumbing industry for 32 years and currently have five staff working for me at Phillip Best Plumbing. Since becoming available, we've purchased a number of CWT water systems to stop calcium deposits building up in a range of different piping systems. These deposits create many unwanted effects such as clogged pipes and irreversible damage to pipes and other plumbing parts. I found the CWT water treatments to be very effective in high temperature heating systems such as commercial combustion ovens in restaurants and even in a very high temperature heating system at a local abattoir.

There are also huge time savings associated with CWT water systems. Installation time is cut by at least 90% when compared to similar units. The units, which allow scale particles to be washed away, are not only proving to be successful in commercial and industrial applications, but in private homes with scale and rust problems. I installed a CWT system to protect the hydraulic heating system, which lies under the cement slab of our home.

CWT has been a great cost saving unit initiative that will protect your piping system from ongoing scale and rust problems.

Your Phillip Best Plumbing Team





Within three months of installing the CWT water treatment system the iron residual and sludge disappeared. I was staggered by the results. The pipe was completely clear and there were no signs of the iron scale at all. A reliable and clean sprinkler system is very important for us to maintain a healthy garden. The CWT system has saved me an enormous amount of time and money and I'm no longer cleaning sprinkler heads or replacing the solenoids in the reticulation system.

Lance Butcher, Gelorup



Excerpt from our Client List

Alcatel

Bayer-Leverkusen

Beutelsbacher Juice Factory

BOSCH

Block House Restaurant

COSWIG

Daimler Chrysler

Design Hotel Q!

Dynamit Nobel

Eberswalder sausage factory

Freixenet Sparkling Wine

Gegenbauer facility service

General Cement Organization

Grand Hotel Europe

Haecker Gelatine Production

Hartwall Ice Hockey Arena

Holstein Therme Spa

Hotel Cadolzburg

Hotel President

Hotel Terme Dolomiti

McDonald's

koelnmesse

MAN

Mercure Hotel

Meridien Hotel N'Fis

MeridianSpa

Mövenpick Restaurants

Opel

Park Hotel

Pilbara Commercial Laundry

Public service of Munich

Rhein Chemie

Riverview Hospital

Langwedel school

SHELL

Siemens

Staedtler

Starbucks Coffee

St. Joseph Hospital

Südmilch Dairy Farming

University of München

Tim Hortons

VarioPlast

Viessmann

Volkswagen VW Cars

White Castle

Wolfies Waterfront Grill

and many more ...









































Water as it should be

Models and sizes

	Residential Line		Commercial Line			Industrial Line	
	Vulcan 3000	Vulcan 5000	Vulcan S10	Vulcan S25	Vulcan S100	Vulcan S250	Vulcan S500
Max. pipe diameter	1¹/₂" 38 mm	2" 50 mm	3" 76 mm	4" 100 mm	6" 150 mm	10" 250 mm	20" 500 mm
Max. capacity	800 gph 3000 l/h	1350 gph 5000 l/h	45 gpm 10 m³/h	110 gpm 25 m³/h	450 gpm 100 m³/h	1100 gpm 250 m³/h	2200 gpm 500 m³/h
Voltage	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt	24 Volt
Wattage	2.0 Watt	2.0 Watt	2.25 Watt	2.25 Watt	2.5 Watt	2.75 Watt	3.25 Watt
Impulse bands	2 x 3′ 3″ 2 x 1 m	2 x 3′ 3″ 2 x 1 m	2 x 3′ 3″ 2 x 1 m	4 x 6′ 7″ 4 x 2 m	6 x 13′ 2″ 6 x 4 m	8 x 32' 9" 8 x 10 m	10 x 98′ 5″ 10 x 30 m
Band width	0.4" 10 mm	0.4" 10 mm	0.8" 20 mm	0.8" 20 mm	0.8" 20 mm	0.8" 20 mm	0.8" 20 mm
Measurements	3.1/5.1/1.2" 80/130/30 mm	3.3/5.9/1.2" 85/150/30 mm	4.7/7.5/1.6" 120/190/40 mm	4.9/7.9/1.6" 125/200/40 mm	5.6/9.4/1.6" 150/240/40 mm	7.9/11.6/2.0" 200/295/50 mm	8.7/12.6/2.0" 220/320/50 mm
Frequency range	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz	3-32 kHz
Required space	11" 300 mm	1' 2" 350 mm	1' 8" 500 mm	1' 12" 600 mm	3' 11" 1200 mm	8′ 3″ 2500 mm	16′ 5″ 5000 mm
Programs	1	1	3	5	10	10	10

